



---

## THE SAFETY LOCK

The ABUS 76 Series has an 8-pin cylinder and is available with more than 200,000 true key differs, making it the first safety padlock to offer this.

The protected keyway eliminates cross-keying and reduces the risk of employee injury, company liability, and code violations. Available in a variety of colors and shackle options. These padlocks also meet OSHA standard lockout/tagout guidelines, and its protected keyway eliminates cross-keying, reducing risk for employees.

---

## Technologies

- Body insulated
- Solid aluminum core: Lightweight and durable
- Precision 8-pin cylinder for the very high number of 150,000 guaranteed keyed different bittings
- Large, extremely breaking resistant key with V-shape cuts ensures high precision
- Automatic locking for user convenience
- 9 different shackle options
- One key according to lockout requirement: one worker, one lock, one key
- Key-retaining: Lock retains key until locked

## Use and application

- Safety at work

## Variants

- 10 colors: red, yellow, green, blue, orange, purple, white, black, grey, brown

# 76IB/40 orange

- Shackle versions in different lengths: steel, sheathed steel, stainless steel or non-conductive plastic
- Cable versions with flexible wire instead of rigid shackle: stainless steel cable with plastic coating, 8 inches or 16 inches long
- Available keyed alike
- Integration into key systems possible

## Technical data - 76IB/40 orange

|                        |               |
|------------------------|---------------|
| Depth e                | 55/64 inch    |
| Height f               | 3 1/2 inch    |
| Horizontal clearance b | 25/32 inch    |
| Keyed alike            | No            |
| Locking type           | key           |
| Security card          | No            |
| Shackle diameter d     | 13/64 inch    |
| Vertical clearance c   | 1 17/32 inch  |
| Weight [lbs]           | 0.27 lbs      |
| Width a                | 1 37/64 inch  |
| color                  | orange        |
| color of facets        | orange        |
| EAN                    | 4003318847981 |