

7" Universele testmonitor

Art.-Nr. TVAC10101

Seite 1 von 2



The new 7" Universal Test Monitor is the ideal helper for all video projects. Conveniently transportable and with a battery life of up to 10 hours, the monitor delivers the desired measurement data everywhere - to video image, network, voltage and cable. In addition to the handy design, the combination of touchscreen and control buttons makes the test monitor particularly user-friendly. The test monitor is Android-based, acts like an ordinary Android tablet and becomes your mobile computer. Designed specifically for the maintenance and installation of IP network cameras, analog TVI, CVI, AHD and CVBS cameras, it offers many more with preinstalled applications:

A network tool with IP address search or PING and PoE measurement function and much more is available for the installation and configuration of IP networks.

Use the test monitor as a mobile power supply for your device, whether directly via PoE with up to 24 W, one of the two 12V and up to 3A plug connectors, or the USB interface with 5V and up to 2A. The latter is ideal for charging your smartphone.

An HDMI input and output make the test monitor even more versatile.

Use the cable tester to check the wiring and length of network cables or to detect damage.

Create snapshots and video sequences to document your installation.

You always have your important documents in digital form with you or simply create them with the familiar Android Office programs.

Increase your productivity by installing your familiar and popular Android applications on your Universal Test Monitor.

An integrated LED lamp helps you to work in poorly lit environments.

The range of functions of the 7" Universal Test Monitor makes it an essential tool for installers and technicians, which you no longer want to miss.

Note: System language is English.

Technologieën

- Universele testmonitor voor het onderhoud en de installatie van IP-netwerkcamera's en analoge TVI-, CVI-, AHD- en CVBS-camera's
- 7-inch touch-display met hoge resolutie met 1.280 x 800 pixels
- Ondersteunt 4K H.264- en 4K H.265-streams
- Compatibel met externe fabrikanten

7" Universele testmonitor

Art.-Nr. TVAC10101

Seite 2 von 2

- Met netwerktools om het netwerk te onderhouden en te verifiëren
- Geïntegreerde PoE-voeding met 24 W op de LAN-poort
- Geïntegreerde mobiele voeding voor apparaten en geïntegreerde USB-voeding voor USB-apparaten
- Wi-Fi en Wi-Fi hotspot-functie
- Met kabeltester voor het controleren van netwerkkabels
- Gegevensback-up op SD-kaart mogelijk (schermafbeeldingen / video's / documenten)

Technische gegevens - 7" Universele testmonitor

Aansluitingen	1 x HDMI-ingang, 1 x HDMI-uitgang, 1 x BNC-ingang (TVI, CVI, AHD, CVBS), 1 x BNC-ingang (SDI), 1 x BNC-uitgang (CVBS), 1 x RJ45 (LAN), 2 x RJ45 (PSE-invoer), 1 x RJ45 (UTP-poort), 1 x 3,5 mm-aansluiting (audio-invoer), 1 x 3,5 mm-aansluiting (audio-uitvoer), 1 x DC Ingang (12 V, 2 A), 2 x DC-uitgang (12 V, 3 A), 1 x USB-uitgang (5 V, 2 A), 1 x RS485
Afmetingen	(b x h x d) 231 x 172 x 52 mm
Batterij - type	7,6 V / 7800 mAh, Li-ion Polymer
Beeldschermdiagonaal	7 in
Breedte	231 mm
Hoogte	172 mm
Lengte	52 mm
Luidspreker	Ja
Max. bedrijfstemperatuur	50 °C
Min. bedrijfstemperatuur	-10 °C
Monitortype	IPS touch-display
Nettogewicht	0,945 kg
Resolutiemodi	1280 x 800
Stroomopname	2.000 mA
Taal OSD	GB, FR, IT
Taal handleiding	DE, GB
Videosysteem	IP, TVI, CVI, AHD, CVBS
Voedingsspanning DC	12 V