

# Wired NC Opening Detector (white)

Art.-Nr. FU7350W

Seite 1 von 2



The opening detector is a magnetic contact for protecting doors and windows. Unauthorised opening is detected and reported to the alarm center. The opening detector consists of a magnetic contact (reed) and a magnet. These are fitted parallel, in front of, or at right angles to each other at a maximum distance of 13 mm apart. The electric circuit of this NC opening detector is normally closed (NC). If the distance between the reed and the magnet increases, the circuit is broken and an alarm reported. The optimum installation location is the middle of the door or window frame. It can also be fitted to the bottom of the window frame if a particular window with a magnetic contact is to be tilted open. The detector is suitable for both flush and surface-mounted installation. The opening detector is available in white and brown.

## Technologies

- For reliable protection of windows and doors (perimeter protection)
- Magnetic contact suitable for wall mounting and flush mounting
- Opening detector consisting of magnetic contact and magnet
- Incl. 2 m cable (2-wire), mounting enclosure, shims and fixing screws
- NC switching contact

## Technical data - Wired NC Opening Detector (white)

|                           |  |
|---------------------------|--|
| Cable length              | 2 m  |
| Cable type                | 2-core                                     |
| Colour                    | white                                      |
| Connections               | NC, max. contact capacity 100 V/5 W/0.05 A |
| Dimensions                | (WxHxD) 11x12x48 mm                        |
| External field protection | No   |
| Height                    | 12 mm                                      |
| Housing material          | ABS  |

# Wired NC Opening Detector (white)

Art.-Nr. FU7350W

Seite 2 von 2

---

## Technical data - Wired NC Opening Detector (white)

|                            |                                    |
|----------------------------|------------------------------------|
| Installation location      | Integration / surface mounting     |
| Installation type          | Surface mounting/recessed mounting |
| Length                     | 48 mm                              |
| Max. operating temperature | 50 °C                              |
| Min. operating temperature | -10 °C                             |
| Sensor type                | Reed contact                       |
| Type of detection          | Magnetic field measurement         |
| VdS class                  | none                               |
| Width                      | 11 mm                              |