

# Terxon Wireless Remote Control

Art.-Nr. FU8150

Seite 1 von 2



The wireless remote control is an optional accessory for Terxon MX/LX and Secvest 2WAY. This enables you to operate the system at the simple touch of a button from anywhere, inside or outside your property. It is not necessary to go to the control panel - as the wireless control with a range of 30 metres offers you maximum flexibility and utmost convenience.

In combination with the Secvest 2WAY, individual parts of the alarm panel can also be switched. The remote control is also equipped with a panic function - this allows you to trigger a predefined alarm manually and send (depending on the programming of the system) a message to emergency services or any telephone number. In this way, the remote control offers you a way of getting help quickly in the event of an emergency. When you press two buttons simultaneously, an emergency alarm is triggered which works, for example, as a "silent alarm" and ensures that any perpetrators are not provoked. The remote control battery has a service life of approx. 24 months. VSÖ and INCERT certifications stand for certified quality.

## Technologies

- Arms and disarms the alarm panel or individual partitions
- Suitable for use with Terxon MX/LX in conjunction with corresponding wireless upgrade
- Operation of several switching outputs possible
- With panic function

## Technical data - Terxon Wireless Remote Control

Battery - type	3V LiMnO <sub>2</sub> CR-2032
DC voltage supply	3 V
Dimensions	(WxHxD) 34x60x15 mm
Environmental class	II
Height	60 mm
Housing material	ABS
Length	15 mm
Max. operating temperature	55 °C
Max. transmission range (building)	30 m

# Terxon Wireless Remote Control

Art.-Nr. FU8150

Seite 2 von 2

---

## Technical data - Terxon Wireless Remote Control

Max. transmission range (free field)	100 m
Min. operating temperature	-10 °C
Net weight	0,017 kg
Radio frequency	868,6625 MHz
Radio power	1 mW
Security level	2
Width	34 mm