

Wireless Display Module

Art.-Nr. FU8403

Seite 1 von 2



The wireless display module provides a quick overview of the status of the Secvest detectors in the house. You can see at a glance whether a detector or a window is open or closed. The module has a convenient status display for the FTS 96 E wireless window protection system and the Secvest wireless magnetic contact detectors - even in stand-alone mode without the alarm panel. However, if the window protection systems are operated in combination with a Secvest 2WAY, the display module is an important supplement: window protection system and wireless magnetic contact detectors can be taught-in to the display module and the alarm panel at the same time.

Technologies

- 16 individually programmable display channels
- Compatible with mechatronic and Secvest wireless opening detectors
- 2 LED status indicators
- Standalone solution for displaying the status of connected detectors

Technical data - Wireless Display Module

| | |
|---------------------------------|------------------------|
| Compatible with | Secvest, Terxon |
| DC voltage supply | 12 V |
| Dimensions | (WxHxD) 135x220x45 mm |
| Display | 18 LED status displays |
| Environmental class | I |
| Height | 220 mm |
| Housing material | ABS |
| Length | 45 mm |
| Max. operating temperature | 50 °C |
| Max. receiving range (building) | 30 m |

Wireless Display Module

Art.-Nr. FU8403

Seite 2 von 2

Technical data - Wireless Display Module

| | |
|-----------------------------------|---------|
| Max. receiving range (free field) | 100 m |
| Min. operating temperature | 0 °C |
| Modulation | FM |
| Net weight | 0,52 kg |
| Power consumption | 150 mA |
| Radio frequency | 868 MHz |
| Width | 135 mm |