

10 m Preassembled Video Combination Cable

Art.-Nr. TVAC40110

Seite 1 von 1



Save time during installation!

This pre-assembled combined video cable is an extremely practical accessory for analogue video surveillance cameras. It can be used both for video signal transmission and power supply. Not only are video signal and power supply combined in one cable, the cable is already pre-assembled and ready to connect, saving you the time-consuming tasks of stripping wires, clamping and crimping. The pre-assembled combined video cable is available in lengths of 10m (TVAC40110), 20m (TVAC40120) and 30m (TVAC40130).

Note: Pre-assembled video cables TVAC40110, TVAC40120 and TVAC40130 are only compatible with the analogue HD cameras HDCC31500 and HDCC41500.

Technologies

- Video signal and power supply in combined in one cable
- Pre-assembled BNC and DC connections
- Suitable for all cameras with BNC socket (female) and power supply connection (male)
- 10 m cable length

Technical data - 10 m Preassembled Video Combination Cable

| | |
|----------------------------|---------------------------|
| Cable length | 10 m |
| Cable type | Combined video cable |
| Connection type | BNC (male) - BNC (female) |
| DC voltage supply | 12 V |
| Damping | 0.53 dB |
| Diameter | 6 mm |
| Housing material | PVC |
| Insulation | PE |
| Intended use | indoors |
| Max. operating temperature | 60 °C |
| Min. operating temperature | -10 °C |
| Outer diameter | 6 mm |