



This reliable and robust cylinder provides secure, controlled and convenient access. It was specifically designed for use with panic doors with automatic reset of the locking nose. It is operated using the read-protected ABUS Seccor chip key.

Technologies

- Electronic cylinder with chip key reader
- Internal mechanical components and electronics for maximum durability
- Simple installation without drilling for easy retrofitting
- Infinitely variable length adjustment by means of profile cylinder adapter
- Acoustic signal

Technical data - ZL Standard

| | |
|-------------------------------------|---|
| Area of application | Doors with a PZ mortise lock (no free-wheel function) |
| Backup power supply | ESE (see general accessories) |
| Battery - type | CR2 |
| Colour | Stainless steel |
| Combination code | No |
| Comfort lock | Yes |
| Cutting the axle to length inwards | 15–61 mm mm |
| Cutting the axle to length outwards | 15–66 mm mm |
| DC voltage supply | 3 V |
| Depth inside (incl. knob) | 49 mm |
| Depth outside (incl. knob) | 41 mm |

Technical data - ZL Standard

| | |
|-------------------------------------|--|
| Drill protection | Standard |
| Electronics | Standard |
| Inside length | 96 mm |
| Language of instructions | DE |
| Language packing | DE |
| Length adjustment | yes, infinitely variable adjustment through axis cut-off |
| Locking media | ACS |
| Logging and time function | No |
| Material | Die-cast zinc |
| Max. humidity | 80 % |
| Max. number of locking media | 511 |
| Max. operating temperature indoors | 60 °C |
| Max. operating temperature outdoors | 60 °C |
| Min. operating temperature indoors | -10 °C |
| Min. operating temperature outdoors | -20 °C |
| Net weight | 0 kg |
| OSD language | German |
| Opening time can be set | No |
| Outside length | 94 mm |
| Permanent access | Yes |
| Programming | Via Prog ACS or PELT + Prog ACS or SKM |
| Reader type | Chip key reader |
| Signalling | Audible |
| Width inside | 38 mm |
| Width outside | 32 mm |
| ZAAP | No |