

# SLT Standard VdS B stainless steel

Art.-Nr. 501595

Seite 1 von 2



This SLT series electronic security fitting ensures increased intrusion protection and more convenient access, and enables keyless opening thanks to code entry. It is operated by entering a code on the coverable keypad or by using the ABUS Seccor chip key as usual. Entering a valid code on the keypad enables keyless entry and is a safer option in case the key is lost or the door slams shut unexpectedly. The protocol and time function makes it possible to save events and allocate rights linked to the time of day or the day of the week. The fitting has additional plating for even greater protection against break-ins.

## Technologies

- Mechatronic security fitting with code keypad, chip key reader and logging function
- Increased security for your front door: Intrusion protection and security in case of key loss and accidental closing of the front door
- Convenient and flexible door opening thanks to code entry
- Acoustic signal

## Technical data - SLT Standard VdS B stainless steel

|                                 |  |
|---------------------------------|--|
| Alphanumeric keypad             | Yes                                    |
| Annual profiles                 | No                                     |
| Area of application             | Doors with a PZ mortise lock and lever |
| Backup power supply             | ESE (see general accessories)          |
| Colour                          | Stainless steel                        |
| Combination code                | Yes                                    |
| Comfort lock                    | Yes                                    |
| Drill protection                | Security                               |
| Electronics                     | Default                                |
| Emergency power supply possible | Yes                                    |

# SLT Standard VdS B stainless steel

Art.-Nr. 501595

Seite 2 von 2

## Technical data - SLT Standard VdS B stainless steel

|                                     |  |
|-------------------------------------|--|
| Event memory                        | No                                     |
| Language of instructions            | EN                                     |
| Language packing                    | EN                                     |
| Locking media                       | ABUS Seccor chip key                   |
| Logging and time function           | No                                     |
| Material                            | Die-cast zinc                          |
| Max. humidity                       | 80 %                                   |
| Max. number of locking media        | 511                                    |
| Max. operating temperature indoors  | 60 °C                                  |
| Max. operating temperature outdoors | 60 °C                                  |
| Min. operating temperature indoors  | -10 °C                                 |
| Min. operating temperature outdoors | -20 °C                                 |
| Net weight                          | 3,13145 kg                             |
| Number of cycles/battery            | 50.000                                 |
| Number of digits Keyboard codes     | 4-digit to 6-digit                     |
| OSD language                        | English                                |
| Permanent access                    | Yes                                    |
| Programming                         | Per Prog ACS or PELT + Prog ACS or SKM |
| Reader type                         | Chip key reader and code entry         |
| Weekly profiles                     | No                                     |
| ZAAP                                | No                                     |