

EL proximity entry unit

Art.-Nr. 501625

Seite 1 von 2



The EL entry unit from ABUS Security-Center signifies efficiency and performance. In spite of the compact construction and the discreet design, this wall reader opens up numerous possibilities in combination with the SG control units or the AE255F evaluation units. This enables the operation of electric circuits such as motorized locks, lifts or automatic doors to be controlled via the insertion of a valid ABUS Seccor chip key or verification with a valid proximity medium. The EL entry unit is also suitable for activation of electrical door openers.

Technologies

- Entry unit with chip key and proximity reader for wall installation
- Additional reader for contact-free transponder
- For connection to control units (SG-Vario, SG-Basic) for control of electric door openers, motorized locks, lifts, cabinets etc.
- For connection to evaluation units (AE255F), for arming/disarming burglar alarm systems
- Acoustic signal

Technical data - EL proximity entry unit

Colour	Stainless steel
Dimensions	Outside: 95 x 56 x 23 mm mm
Environmental conditions	Temperature min./ max.: -20/ 60, max. humidity: 80%
Height	95 mm
Item abbreviation	EL-LPxA-0
Length	23 mm
Locking media	ACS, T-Prox/K-Prox
Power supply	Control unit (SGP-Vario, SG-Basic) or AE255F evaluation unit
Programming	Via programming key and/or PELT or SKM with TG-SKM
Protection class IP Outdoor	44

EL proximity entry unit



Security Tech Germany

Art.-Nr. 501625

Seite 2 von 2

Technical data - EL proximity entry unit

Reader type	Chip key and proxy reader
Signalling	Acoustic
Width	56 mm