

# Extension LCD Keypad for Terxon

Art.-Nr. AZ4111

Seite 1 von 2



The LCD Keypad is an extension module for the Terxon SX and Terxon MX. Installed near the entrance door, it allows you to quickly operate your alarm panel. The LCD keypad is connected to the Terxon SX/MX via a 4-wire bus cable. Up to 4 control units can be integrated into the alarm system. Arranged in various parts of your building, these extension modules provide additional convenience. The system can be conveniently activated or deactivated via any keypad using a PIN code and proximity chip key. The status of the alarm control panel is also displayed on the plain text display of the control unit. You can conveniently view and, of course, change system settings, programming and the 250x event memory of the Terxon S/M. The LCD keypad is designed in an elegant white color. Thus, it is not only an enhancement for each entrance area, but it is also optically in line with the wireless components of the Secvest 2WAY.

## Technologies

- For operating and programming the alarm panel
- Suitable for interior areas and protected outer areas
- Operate your alarm panel with PIN code or proximity chip key
- Integrated proximity chip key reader

## Technical data - Extension LCD Keypad for Terxon

Certifications	INCERT, VSÖ, F&P, NCP
Connections	4-core bus, screw terminal for additional tamper contact, panic alarm button, and button for manually ending the exit delay
DC voltage supply	12 V
Dimensions	(WxHxD) 113x90x23 mm
Environmental class	II
Height	90 mm
Housing material	ABS
IP protection class	54

# Extension LCD Keypad for Terxon

Art.-Nr. AZ4111

Seite 2 von 2

## Technical data - Extension LCD Keypad for Terxon

Installation location	Indoors and protected outdoor areas
Integrated siren	Integrated buzzer
Length	23 mm
Max. humidity	94 %
Max. operating temperature	55 °C
Min. operating temperature	-10 °C
Net weight	0,2 kg
Power consumption	30 mA
Sabotage monitoring	Yes
Security level	2
Width	113 mm

## Technical data - LCD Keypad For Terxon SX / MX

Connections	4-core bus, screw terminal for additional tamper contact, panic alarm button, and button for manually ending the exit delay
DC voltage supply	12 V
Depth	30 mm
Dimensions	(WxHxD) 135x135x30 mm
Display	alphanumeric LCD-Display 2lines
Environmental class	II
Height	135 mm
Housing material	ABS
IP protection class	54
Installation location	Indoors and protected outdoor areas
Integrated siren	1
Length	30 mm
Max. humidity	94 %
Max. operating temperature	55 °C
Min. operating temperature	-10 °C
Net weight	0,2 kg
Power consumption	30 mA
Sabotage monitoring	Yes
Security level	2
Width	135 mm
EAN	4043158015713