

Secvest Wireless Magnetic Contact CC (brown)

Art.-Nr. FUMK50000B

Seite 1 von 2



Reliable alarm triggering in the event of intrusion

The wireless opening detector detects and reports the unauthorised opening of doors and windows using a magnetic contact. In such cases, it informs the wireless alarm panel, which then triggers a corresponding alarm.

Detection and reporting

This product consists of a detector and a magnet. These components are mounted parallel to each other on the moving part of the window or door and on the window or door frame. The detector triggers as soon as the distance between the two contact points is increased when the window or door is opened. The components can be mounted on the bottom window frame in order to allow a window to be tilted open without disrupting the magnetic contact.

Even greater protection with additional wired alarm zones

The wireless opening detector also allows the wiring of additional detectors in order to effectively enhance intrusion protection. The detector can be connected to a passive glass breakage detector, for example, which can be mounted to the window pane and detects window breakages. The wireless opening detector for the Secvest wireless alarm system is available in white and brown.

Technologies

- Reliably detects opening of windows and doors
- Connection option for additional wired detectors
- Can be used as a wireless module
- Tamper monitoring

Secvest Wireless Magnetic Contact CC (brown)

Art.-Nr. FUMK50000B

Seite 2 von 2

Technical data - Secvest Wireless Magnetic Contact CC (brown)

| | |
|---|----------------------------|
| Battery - max. battery life | 2 y |
| Battery - type | 3V CR2 Li/MnO ₂ |
| Certifications | VdS home, EN 50131 Grade 2 |
| Colour | brown |
| Compatible with | Secvest, Terxon, BUM060040 |
| Connections | Screw terminal (CC) |
| DC voltage supply | 3 V |
| Dimensions | (WxHxD) 33x89x29 mm |
| Environmental class | I |
| Height | 89 mm |
| Housing material | ABS |
| Installation location | Windows, doors |
| Length | 29 mm |
| Max. operating temperature | 55 °C |
| Max. transmission range (building) | 30 m |
| Max. transmission range (free field) | 100 m |
| Min. operating temperature | -10 °C |
| Modulation | FM |
| Net weight | 0,076 kg |
| Power consumption | 30 mA |
| Radio frequency | 868,6625 MHz |
| Radio power | 10 mW |
| Sabotage monitoring | Yes |
| Security level | 2 |
| Sensor type | Reed contact |
| Status display | Yes |
| Type of detection | Magnetic field measurement |
| VdS class | none |
| Voltage monitoring | Yes |
| Width | 33 mm |