

Secvest Wireless Window Bar Lock FOS 550 E - AL0145 (brown)

Art.-Nr. FUFT50032B Seite 1 von 2



Active intrusion protection for windows and French doors

The VdS-approved FOS 550 E wireless window bar lock actively secures windows and French doors. The dual-point automatic locking system and effective magnetic field sensors prevent intruders from entering with a pressure resistance of up to one tonne and report even the first attempt at opening to the Secvest alarm panel. The Secvest wireless window bar lock is suitable for windows and French doors with turning and tilt-and-turn fittings that open inwardly, and is available in white and brown.

Technologies

- Active intrusion protection (immediately detects break-in attempts)
- With automatic locking system ("window closed" = "window secured")
- Two locking points with pressure resistance of over one tonne
- · Suitable for windows and French doors with turning and tilt-and-turn fittings that open inwardly

Technical data - Secvest Wireless Window Bar Lock FOS 550 E - AL0145 (brown)

Battery - max. battery life	2 y
Battery - type	2 x 1.5 V LRO3 AAA alkaline batteries, Varta Industrial / Industrial Pro, Duracell
	Industrial, Panasonic Powerline
Certifications	VdS (mechanics)
Colour	brown
Compatible with	Secvest, BUM060040
Connections	Clamping terminal
DC voltage supply	3 V
Environmental class	II
Height	50 mm
Housing material	ABS Stainless Steel



Secvest Wireless Window Bar Lock FOS 550 E - AL0145 (brown)

Art.-Nr. FUFT50032B Seite 2 von 2

Technical data - Secvest Wireless Window Bar Lock FOS 550 E - AL0145 (brown)

Installation location	Windows and French windows
Length	170 mm
Locking number	AL0145
Max. operating temperature	55 °C
Max. transmission range	30 m
(building)	
Max. transmission range (free	100 m
field)	
Min. operating temperature	-10 °C
Modulation	FM
Radio power	10 mW
Sabotage monitoring	Yes
Sensor type	Magnetic switch and magnetic field sensor system
Type of detection	Magnetic field measurement
VdS approval no.	M 197093
VdS class	other
Voltage monitoring	Yes
Width	32 mm