

# Secvest Wireless Window Bar Lock FOS 550 E - AL0145 (brown)

Art.-Nr. FUFT50032B

Seite 1 von 2



Active intrusion protection for windows and French doors

The VdS-approved FOS 550 E wireless window bar lock actively secures windows and French doors. The dual-point automatic locking system and effective magnetic field sensors prevent intruders from entering with a pressure resistance of up to one tonne and report even the first attempt at opening to the Secvest alarm panel. The Secvest wireless window bar lock is suitable for windows and French doors with turning and tilt-and-turn fittings that open inwardly, and is available in white and brown.

## Technologies

- Active intrusion protection (immediately detects break-in attempts)
- With automatic locking system ("window closed" = "window secured")
- Two locking points with pressure resistance of over one tonne
- Suitable for windows and French doors with turning and tilt-and-turn fittings that open inwardly

## Technical data - Secvest Wireless Window Bar Lock FOS 550 E - AL0145 (brown)

|                             |  |
|-----------------------------|--|
| Battery - max. battery life | 2 y  |
| Battery - type              | 2 x 1.5 V LR03 AAA alkaline batteries, Varta Industrial / Industrial Pro, Duracell Industrial, Panasonic Powerline |
| Certifications              | VdS (mechanics)  |
| Colour                      | brown  |
| Compatible with             | Secvest, BUM060040   |
| Connections                 | Clamping terminal  |
| DC voltage supply           | 3 V  |
| Environmental class         | II   |
| Height                      | 50 mm  |
| Housing material            | ABS Stainless Steel  |

# Secvest Wireless Window Bar Lock FOS 550 E - AL0145 (brown)

Art.-Nr. FUFT50032B

Seite 2 von 2

## Technical data - Secvest Wireless Window Bar Lock FOS 550 E - AL0145 (brown)

|                                      |  |
|--------------------------------------|--|
| Installation location                | Windows and French windows                       |
| Length                               | 170 mm   |
| Locking number                       | AL0145   |
| Max. operating temperature           | 55 °C  |
| Max. transmission range (building)   | 30 m   |
| Max. transmission range (free field) | 100 m  |
| Min. operating temperature           | -10 °C   |
| Modulation                           | FM   |
| Radio power                          | 10 mW  |
| Sabotage monitoring                  | Yes  |
| Sensor type                          | Magnetic switch and magnetic field sensor system |
| Type of detection                    | Magnetic field measurement                       |
| VdS approval no.                     | M 197093   |
| VdS class                            | other  |
| Voltage monitoring                   | Yes  |
| Width                                | 32 mm  |