Smartvest Wireless Siren



Art.-Nr. FUSG35000A Seite 1 von 2



To be able to provide alarming both indoors and outdoors, the Smartvest Wireless Siren is fitted with a loud siren (up to 100dB) and a red LED strobe light. Battery operation (battery life: up to two years) means no wiring is required during installation; when the battery is low, the alarm panel is notified immediately. To be able to guarantee real security, the Smartvest Wireless Siren is fitted with tamper protection in the form of an anti-removal wall contact.

Technologies

- Smartvest extension for sounding alarms indoors and outdoors
- Quick and cable-free installation without the need for wires thanks to battery operation
- High-volume siren (up to 100 dB) and red LED strobe light for alarms with deterrent effect
- Sturdy, weatherproof siren (IP44)
- Automatic supervision, with functional tests repeated daily and feedback sent to the Smartvest alarm control panel
- Low battery notification sent to the Smartvest alarm control panel
- Battery life of up to 2 years
- Tamper protection provided by anti-removal wall contact

Technical data - Smartvest Wireless Siren

Alarming	Acoustic warning signal
Area of application	Outside / Inside
Battery - battery operation	Yes
Battery - max. battery life	1 y
Battery - quantity	4
Battery - type	C (1,5V)
Colour	White
Compatible with Secvest	No
Compatible with Smartvest	Yes





Art.-Nr. FUSG35000A Seite 2 von 2

Technical data - Smartvest Wireless Siren

DC voltage supply	5 V
Dimensions	(B x L x H) 112 x 122 x 300 mm
Gross weight	0,19 kg
Housing material	Plastic
IP protection class	44
Light source	LED
Luminous colour	Red
Max. humidity	80 %
Max. operating temperature	50 °C
Min. humidity	10
Min. operating temperature	-10 °C
Net weight	0,82 kg
Plug type	DC-plug: 3,5 x 1,35mm
Power consumption	200 mA
Radio frequency	868 MHz
Radio modulation	FSK
Sound pressure	100 dB
Standby power consumption	0,2 mA
Tamper protection	Yes
Transmission power	4,5 dBm
Wireless range	(Depending on installation) 30 - 100 m