

2 Network Outdoor Cameras + Accessory

Art.-Nr. TVVR36020S

Seite 1 von 2

Technical data - 2 Network Outdoor Cameras + Accessory

Alarming	E-Mail
Amplifier control	AGC
Backlight compensation	BLC, DWDR
Camera type	Day/night
Certifications	CE, RoHS, REACH
Connections	1 x RJ45, 1 x DC
DC voltage supply	12 V
Day/night switching	Electromechanical IR-cut filter, Color/B-W
Digital zoom	Yes
Electronic shutter	1/3 - 1/100000 s
Focal length	4 mm
Frame rate	1280 x 960 @ 25 fps, 1280 x 720 @ 25
Height	60 mm
Horizontal viewing angle	73,1 °
IP protection class	66
IR LEDs	30
IR range (up to)	10 m
Image sensor	1/3" Progressive Scan CMOS
LAN network access	RJ-45 Ethernet 10/100 Base-T
Language of instructions	DE, UK, FR, NL, DK, ES, IT, PL, SWE
Language packing	DE, UK, FR, NL, DK, ES, IT, PL, SWE
Length	145 mm
Max. operating temperature	50 °C
Max. resolution @ frame rate	1280 x 960 @ 25 fps
Min. operating temperature	-20 °C
Minimum illumination (IR)	0 lx
Minimum illumination (colour)	0,1 lx
Motion detection	8 zones
Net weight	0,5 kg
Network camera protocols	TCP/IP, ICMP, HTTP, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, 802.1X, IPv6, Bonjour
Noise reduction	DNR
ONVIF	Profile S
OSD language	DE, UK, FR, NL, DK, ES, IT, PL, SWE
Pixels (effective)	1280(H) x 960(V) pixel
Pixels (total)	1280(H) x 960(V) pixel
Power consumption	580 mA

2 Network Outdoor Cameras + Accessory



Art.-Nr. TVVR36020S

Seite 2 von 2

Technical data - 2 Network Outdoor Cameras + Accessory

Resolution modes	Main Stream: 1280 x 960, 1280 x 720, 704 x 576, 640 x 480
Software	ABUS VMS Express, IPCam App
Supported browsers	Mozilla Firefox, Safari or Internet Explorer 6.x and higher
Technology	IP
Video compression	H.264, MJPEG
Video system	IP
WLAN network access	IEEE802.11b, 802.11g, 802.11n
White balance	Yes
Width	61 mm