

# 2 Network Outdoor Dome Cameras + Accessory

Art.-Nr. TVVR36521S

Seite 1 von 2

## Technical data - 2 Network Outdoor Dome Cameras + Accessory

Alarming	E-Mail
Amplifier control	AGC
Backlight compensation	Soft-WDR
Camera type	Day/night
Certifications	CE, RoHS, Reach
Connections	1 x RJ45, 1 x DC
DC voltage supply	12 V
Electronic shutter	1/3 - 1/100000 s
Encryption	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK, WPS
Focal length	4 mm
Frame rate	25 fps @ 1280x960, 25 fps @ 1280x720
Height	82 mm
Horizontal viewing angle	69,4 °
IP protection class	66
IR LEDs	30
IR range (up to)	10 m
Image sensor	1/3" Progressive Scan CMOS
LAN network access	RJ-45 Ethernet 10/100 Base-T
Language of instructions	DE, UK, FR, NL, DK, PL, RU, SWE, IT, ES
Max. operating temperature	50 °C
Max. resolution @ frame rate	1280 x 960 @ fps
Min. operating temperature	-10 °C
Minimum illumination (IR)	0 lx
Minimum illumination (colour)	2 lx
Motion detection	3 zones
Net weight	500 kg
Network camera protocols	IPv4, IPv6, TCP/IP, HTTP, UPnP, RTP/RTSP, SMTP, DHCP, NTP, DNS, DDNS
Noise reduction	DNR
ONVIF	Profile S
OSD language	DE, UK, FR, NL, DK, PL, RU, SWE, IT, ES
Pixels (effective)	1280 x 960 pixel
Pixels (total)	1280 x 960 pixel
Power consumption	580 mA
Private zones	4
Resolution modes	1280 x 960, 1280 x 720, 704 x 576, 352 x 288, 176 x 144
Software	ABUS VMS, IPCam App (iOS)
Supported browsers	Internet Explorer, Mozilla Firefox, Chrome

# 2 Network Outdoor Dome Cameras + Accessory

Art.-Nr. TVVR36521S

Seite 2 von 2

---

## Technical data - 2 Network Outdoor Dome Cameras + Accessory

Technology	IP
Video compression	H.264, MJPEG
Video system	IP
White balance	AWB
Width	111 mm