

SLT Alarm AE255 VdS C stainless steel

Art.-Nr. 501802

Seite 1 von 2



This SLT series electronic security fitting ensures increased intrusion protection and more convenient access, and enables keyless opening thanks to code entry. It is operated by entering a code on the coverable keypad or by using the ABUS Seccor chip key as usual. Entering a valid code on the keypad enables keyless entry and is a safer option in case the key is lost or the door slams shut unexpectedly. As this SLT security fitting is connected to the AE255 evaluation unit we can offer an even higher security level due to wired transmission. The protocol and time function makes it possible to save events and allocate rights linked to the time of day or the day of the week. The fitting has additional plating for even greater protection against break-ins.

Technologies

- Mechatronic security fitting with code keypad, chip key reader and logging function
- Increased security for your front door: Intrusion protection and security in case of key loss and accidental closing of the front door
- Convenient and flexible door opening thanks to code entry
- Acoustic signal
- Suitable for use with evaluation unit AE255 with door wiring for arming/disarming burglar alarm systems

Technical data - SLT Alarm AE255 VdS C stainless steel

Alphanumeric keypad	Yes
Area of application	Doors with a PZ mortise lock and lever
Backup power supply	ESE (see general accessories)
Certifications	VdS, class C
Colour	Stainless steel
Drill protection	Security, VdS class B
Electronics	AE255
Locking media	ABUS Seccor chip key

SLT Alarm AE255 VdS C stainless steel

Art.-Nr. 501802

Seite 2 von 2

Technical data - SLT Alarm AE255 VdS C stainless steel

Material	Die-cast zinc
Max. humidity	80 %
Max. number of locking media	511
Max. operating temperature indoors	60 °C
Max. operating temperature outdoors	60 °C
Min. operating temperature indoors	-10 °C
Min. operating temperature outdoors	-20 °C
Net weight	0 kg
Number of cycles/battery	50.000
Number of digits Keyboard codes	4-digit to 6-digit
OSD language	English
Permanent access	Yes
Programming	Per Prog ACS or PELT + Prog ACS or SKM
Reader type	Chip key reader and code entry