

CodeLoxx Remote Proximity Protokoll Security

Art.-Nr. CLX-LPXA-RP-10

Seite 1 von 2



Technical data - CodeLoxx Remote Proximity Protokoll Security

Annual profiles	6
Area of application	Doors with PZ mortise lock, multiple locking, panic lock (approved for locking nose with free-wheel function)
Colour	Stainless steel
Combination code	No
DC voltage supply	3 V
Drill protection	Security
Electronics	Remote with logging function
Emergency power supply possible	Yes
Event memory	1000
Inner knob diameter	33 mm
Inner knob length	49 mm
Locking media	ABUS Seccor chip key EM4102, Hitag 1 and Hitag 2 transponder
Logging and time function	Yes
Material	Stainless steel knobs, plastic cap inside
Max. number of locking media	511
Max. operating temperature indoors	60 °C
Max. operating temperature outdoors	60 °C
Min. operating temperature indoors	-10 °C
Min. operating temperature outdoors	-20 °C
Modularly extendible	Yes
Opening time can be set	between 6 and 12 seconds
Outer knob diameter	30 mm
Outer knob length	39 mm
Permanent access	Yes
Programming	Via programming key and/or PELT or SKM with TG-SKM

CodeLoxx Remote Proximity Protokoll Security

Art.-Nr. CLX-LPXA-RP-10

Seite 2 von 2

Technical data - CodeLoxx Remote Proximity Protokoll Security

Protection class IP Indoor	55
Protection class IP Outdoor	55
Reader type	Chip key reader and proximity reader
Signalling	optical
Special design axle	For doors with PZ perforation
Standard length	Length measurement when ordering
Weekly profiles	30
ZAAP	No