

CodeLoxx Standard Proximity Protokoll

Art.-Nr. CLX-LPXA-SP-00

Seite 1 von 2



This premium electronic CodeLoxx cylinder provides more security, control and convenience at your door. It allows for contactless operation for fast and easy access control owing to its proximity function. The cylinder has additional plating for even greater protection against attempted break-ins. The unique modular extension system guarantees maximum flexibility during installation, use or structural changes.

Technologies

- Logging electronic double knob cylinder with chip key reader
- High-quality stainless steel knobs
- Permanent access, time-controlled switching Permanent access (ZAAP)
- Opening time adjustable between 6 and 12 seconds
- Additional reader for contactless transponder

Technical data - CodeLoxx Standard Proximity Protokoll

| | |
|------------------------------------|---|
| Annual profiles | 6 |
| Area of application | Doors with PZ mortise lock, multiple locking, panic lock (approved for locking nose with free-wheel function) |
| Colour | Stainless steel |
| Combination code | No |
| DC voltage supply | 3 V |
| Drill protection | Standard |
| Electronics | Standard with logging function |
| Emergency power supply possible | Yes |
| Event memory | 1000 |
| Inner knob diameter | 33 mm |
| Inner knob length | 45 mm |
| Locking media | ABUS Seccor chip key EM4102/4200, Hitag 1 and Hitag 2 transponder |
| Logging and time function | Yes |
| Material | Stainless steel |
| Max. number of locking media | 511 |
| Max. operating temperature indoors | 60 °C |

CodeLoxx Standard Proximity Protokoll

Art.-Nr. CLX-LPXA-SP-00

Seite 2 von 2

Technical data - CodeLoxx Standard Proximity Protokoll

| | |
|-------------------------------------|--|
| Max. operating temperature outdoors | 60 °C |
| Min. operating temperature indoors | -10 °C |
| Min. operating temperature outdoors | -20 °C |
| Modularly extendible | Yes |
| Opening time can be set | between 6 and 12 seconds |
| Outer knob diameter | 30 mm |
| Outer knob length | 39 mm |
| Permanent access | Yes |
| Programming | Via programming key and/or PELT or SKM with TG-SKM |
| Protection class IP Indoor | 55 |
| Protection class IP Outdoor | 55 |
| Reader type | Chip key reader and proximity reader |
| Signalling | optical |
| Special design axle | For doors with PZ perforation |
| Standard length | Length measurement when ordering |
| Weekly profiles | 30 |
| ZAAP | Yes |