

Analogue HD Dome 3 MPx (2.8–12 mm)

Art.-Nr. HDCC73550

Seite 1 von 2



Analogue HD: Analogue images have never been so clear

The Analogue HD Dome 3 MPx has a high-quality image sensor for the surveillance of indoor and outdoor areas and provides a razor sharp and fluid image for better detail recognition. The Analogue HD Dome 3 MPx with True WDR A high-performance True WDR function ensures evenly lit foregrounds and backgrounds in high-contrast light situations.

24/7 indoor and outdoor surveillance

The automatic day/night switching offered by the improved IR LED technology provides for better image lighting. With its high dust and water protection class (IP67) and protection against vandalism (IK10), the camera is ready for both indoor and outdoor use. Simple installation thanks to the motorised zoom lens and large range of brackets The fine adjustment of the installed camera can be done easily via remote access using the recorder and can, therefore, be installed by just one person. The large range of brackets offers flexibility for any installation location.

Analogue HD technology: Ideal for inexpensive retrofitting

Using the infrastructure already installed offers flexible retrofitting possibilities. Simply exchange the cameras and recorders and get better performance from your existing video surveillance systems. You can continue to use your existing coaxial or 2-wire cable.

The effective IR range will depend on the installation location. If there are surfaces that absorb light or no objects that reflect IR light in the field of view, the IR range will be reduced and/or the video image will be too dark. Reflective objects in the immediate vicinity of the camera (e.g. roof gutter or wall) may also result in the reflection of IR light, which can disturb the image.

Technologies

- 3 MPx Resolution: 1920 x 1536 @ 18 fps

Analogue HD Dome 3 MPx (2.8–12 mm)



Art.-Nr. HDCC73550

Seite 2 von 2

-
- 42 % more image data compared to 2 MPx
 - True WDR effectively compensates for light/dark contrast
 - Easy installation and focussing via remote access with the motorised zoom lens (2.8–12 mm)
 - Powerful IR LED technology for improved illumination of up to 40 m at night
 - Vandalism and weather protected housing (IK10 & IP67)
 - Perfect for retrofitting: Transmission using conventional and existing CCTV infrastructure, such as coaxial or 2-wire cables
 - Cable length of up to 500 m possible without loss
 - Wide variety of holders for straightforward, cost-efficient installation
 - Only compatible with Analogue HD Video Recorder HDCC90001, HDCC90011 and HDCC90021
-