

IP Dome 8 MPx (4K, 2.8 - 12 mm)

Art.-Nr. IPCB78520

Seite 1 von 4



The IP Dome provides video streams in 8 MPx resolution with up to 20 fps. The impact, dust- and water-resistant IP67 / IK 10 housing protects against sabotage and vandalism. Due to the integrated IR LEDs the camera can be used at day and night. Access to the camera is possible any time via app.

Best overview

The motor zoom lens with a focal length of 2.8 - 12 mm provides a horizontal viewing angle of 35°-115 °. Focal length and focusing can be adjusted conveniently and precisely remote via the web interface.

Recording and compatibility

The recording can be done either on an ABUS recorder, 3rd party video management software or locally on a microSD card. Furthermore, the camera is compatible with the ABUS Secvest alarm center and the ABUS access control system wAppLoxx.

Comfortable installation

The IP Dome is mounted on the ceiling or optionally with a bracket on the wall. We recommend our installation box (TVAC31300) and the wall bracket (TVAC31340). The free "ABUS IP Installer" software is available for simple setup in the network. The software finds the camera quickly and easily within the network and supports during the installation process.

Note: The camera does not come with a power supply, as it can be powered via PoE.

The effective IR range will depend on the installation location. If there are surfaces that absorb light or no objects that reflect IR light in the field of view, the IR range will be reduced and/or the video image will be too dark. Reflective objects in the immediate vicinity of the camera (e.g. roof gutter or wall) may also result in the reflection of IR light, which can disturb the image.

IP Dome 8 MPx (4K, 2.8 - 12 mm)

Art.-Nr. IPCB78520

Seite 2 von 4

Technologies

- 8 MPx (4K) Resolution: 3.840 x 2.160 @ 20 fps
- 2.8 - 12 mm motor zoom lens
- Ultra low-light performance for excellent results in low-light environments
- 120 dB WDR function to compensate for image contrasts
- Vandalism and weather protected housing (IK10 & IP67)
- IR LEDs (range up to 30m)
- Supports H.264, H.265, MJPEG (incl. dynamic GOP)
- microSD card slot for internal data storage
- 12 V DC & PoE (802.3af)

Technical data - IP Dome 8 MPx (4K, 2.8 - 12 mm)

Alarm input (NO/NC)	1
Alarm output	1
Alarming	E-Mail, NAS, FTP
Aperture at minimum illumination (colour)	F1.4
Audio	2-Way Audio (Browser, CMS)
Backlight compensation	WDR, BLC, HLC
Camera type	Dome
Colour	RAL9003
Compatible with	NVR, IPCam Plus
Compatible with ABUS Link Station	Yes
Compatible with Secvest	Yes
Compatible with wAppLoxx	Yes
Compatible with wAppLoxx Pro	Yes
Connections	1 x RJ45, 1 x DC, 1 x video output, 1 x audio output, 1 x audio input, 1 x alarm input, 1 x alarm output
DC voltage supply	12 (+/-10 %) V
Day/night switching	ICR/Color/B/W
Design	Dome
Dimensions	(LxBxH) 143x143x100 mm
Dynamic range (WDR)	120 dB
Electronic shutter	1/3 - 1/100000 s
Encryption	HTTPS
Focal length	2,8 – 12,0 mm
Frame rate	1/16, 1/8, 1/4, 1/2, 1, 2, 4, 6, 8, 10, 12, 15, 16, 18, 20, 22, 25, 30 fps

IP Dome 8 MPx (4K, 2.8 - 12 mm)

Art.-Nr. IPCB78520

Seite 3 von 4

Technical data - IP Dome 8 MPx (4K, 2.8 - 12 mm)

Functions	Scene Change Detection
Height	100 mm
Horizontal viewing angle	35 – 115 °
ICR day/night function	Yes
IP protection class	67
IR LEDs	Yes
IR range (up to)	30 m
Image enhancement	WDR, BLC, HLC, 3D DNR, Vertical Display
Image sensor	1/2.5" Progressive Scan CMOS
LAN network access	RJ45 10M/100M self-adaptive
Language of instructions	DE, UK, FR, NL, DK
Length	143 mm
Lens	Motor-Zoom
Max. humidity	95 %
Max. operating temperature	60 °C
Max. resolution @ frame rate	3840 x 2160 @ 20 fps
Microphone	No
Min. operating temperature	-30 °C
Minimum illumination (IR)	0 lx
Minimum illumination (colour)	0,01 lx
Motion detection	8 zones
Net weight	1,2 kg
Network access	RJ45
Network camera protocols	IPv4/v6, HTTP, HTTPS, FTP, SMTP, UPnP, DNS, DynDNS, NTP, RTSP, TCP, UDP, DHCP, ONVIF Profile S, ONVIF Profile G, ABUS Server, Secvest Link
Noise reduction	3D DNR
Number of IR LEDs	10
Number of streams	3
Number of users	32
ONVIF	Profile G, S, T
OSD language	DE, UK, FR, NL, DK
Optical zoom	4,2 x
Other functions	Auto Backup Recording, Secvest Connectivity
Pixels (effective)	3840(H) x 2160(V) pixel
PoE standard	IEEE 802.3af
Power consumption	1.075 mA
Private zones	4
Protection class IK	10

IP Dome 8 MPx (4K, 2.8 - 12 mm)

Art.-Nr. IPCB78520

Seite 4 von 4

Technical data - IP Dome 8 MPx (4K, 2.8 - 12 mm)

Resolution	8 MP
Resolution modes	Stream 1: 3.840 x 2.160 @ 20 fps, Stream 2: 640 x 480 @ 25 fps, Stream 3: 1.280 x 720 @ 25 fps
Simultaneous network access	6
Storage medium	microSD card, 256 GB (opt.)
Supported browsers	IE10, IE11, Mozilla Firefox 30.0+, Chrome 31.0+
Technology	IP
Vertical viewing angle	19 – 60 °
Video Content Analysis (VCA)	Tripwire Detection, Intrusion Detection
Video compression	Stream 1: H.264, H.265, Dynamic GOP, Stream 2: H.264, H.265, MJPEG, Stream 3: H.264, H.265, MJPEG
Video network bandwidth	32 kBit/s - 16 MBit/s
Video system	IP
White balance	AWB, Manual
Width	143 mm