

# Analog HD Mini Dome 5 MPx (2.8 mm)

Art.-Nr. HDCC35500

Seite 1 von 3



**ABUS Analogue HD: Analogue images have never been so clear**

The Analogue HD Mini Dome 5 MPx has a high-quality image sensor for the surveillance of extensive indoor and outdoor areas. This ensures it provides a razor sharp and fluid image, for better detail recognition. The Analogue HD Mini Dome 5 MPx with True WDR A high-performance True WDR function ensures evenly lit foregrounds and backgrounds in high-contrast light situations.

**24/7 indoor and outdoor surveillance**

The automatic day/night switching offered by the improved IR LED technology provides for better image lighting under varying light conditions. The Analogue HD Mini Dome is robust in the face of wind and weather thanks to its IP67 protection class.

**Analogue HD technology: Ideal for inexpensive retrofitting**

Using the infrastructure already installed offers flexible retrofitting possibilities. Simply exchange the cameras and recorders and get better performance from your existing video surveillance systems. You can continue to use your existing coaxial or 2-wire cable.

The effective IR range will depend on the installation location. If there are surfaces that absorb light or no objects that reflect IR light in the field of view, the IR range will be reduced and/or the video image will be too dark. Reflective objects in the immediate vicinity of the camera (e.g. roof gutter or wall) may also result in the reflection of IR light, which can disturb the image.

## Technologies

- 5 MPx Resolution: 2592 x 1944 @ 20 fps
- True WDR effectively compensates for light/dark contrast

# Analog HD Mini Dome 5 MPx (2.8 mm)

Art.-Nr. HDCC35500

Seite 2 von 3

- Fixed lens, 2.8 mm
- Powerful IR LED technology for improved illumination of up to 20 m at night
- Weatherproof (IP67) for outdoor use
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- Perfect for retrofitting: Transmission using conventional and existing CCTV infrastructure, such as coaxial or 2-wire cables
- Cable length of up to 500 m possible without loss
- Wide variety of holders for straightforward, cost-efficient installation

## Technical data - Analog HD Mini Dome 5 MPx (2.8 mm)

Amplifier control	AGC, 3 level
Aperture at minimum illumination (colour)	F1.2
Backlight compensation	True WDR
Camera outputs	1 x BNC
Camera type	Mini Dome
Compatible with Secvest	No
Compatible with wAppLoxx	No
Connections	1 x BNC (HD-TVI), 1 x DC (5.5/2.1 mm)
DC voltage supply	12 V +/-15 % V
Day/night switching	Electromechanical IR cut filter
Design	Mini Dome
Dimensions	(LxWxH) 90x83x80 mm
Dynamic range (WDR)	120 dB
Electronic shutter	1/50 – 1/50000 s
Focal length	2.8 mm
Functions	Motion Detection, Tripwire Detection and Intrusion Detection via DVR
HD-TVI video channels	1
Height	80 mm
Horizontal viewing angle	98.0 °
Housing material	Metal
IP protection class	67
IR LEDs	Yes
IR range (up to)	20 m
Image enhancement	WDR, BLC, ATW, DNR
Image sensor	1/2.7" Progressive Scan CMOS
Length	90 mm
Lens	Fix
Lens mount	M12

# Analog HD Mini Dome 5 MPx (2.8 mm)

Art.-Nr. HDCC35500

Seite 3 von 3

## Technical data - Analog HD Mini Dome 5 MPx (2.8 mm)

Max. humidity	90 %
Max. operating temperature	60 °C
Max. resolution @ frame rate	2592x1944 @ 20 frames/s
Microphone	No
Min. operating temperature	-40 °C
Minimum illumination (IR)	0 lx
Minimum illumination (colour)	0,03 lx
Net weight	0,3 kg
Noise reduction	DNR
Power consumption	480 mA
Private zones	4
Protocols	Coax
Resolution	5 MP
Resolution modes	2592 x 1944
Technology	Analogue HD
Vertical viewing angle	50 °
Video system	HD-TVI, CVI, AHD, FBAS
White balance	ATW, manual
Width	83 mm