

HLT612 for front doors in F1: Aluminum (Handle plate/Door handle)

Seite 1 von 2



HIGH STABILITY

House front doors and flat doors become more secure with this door fitting.

Inadequately secured doors make your home an easy target for burglars. Common security vulnerability: Door cylinders that stick out too far and can be easily unscrewed. Secure your doors with a reliable door fitting. Make your butt and rebated doors more secure with this door hardware. It consists of several layers of steel and can withstand a tensile load of 2.5 tonnes. Extra long steel cams with hardened and tempered special M6 screws increase protection against impact. A steel insert in the outer handle reliably prevents tearing. A secure complete package with VdS and DIN certificate for house front doors (HLT) with a thickness of 52 to 72 millimetres and flat front doors (KLT) with a thickness of 37 to 47 millimetres.

Technologies

- Certified according to DIN EN 1906 SK 2 and DIN 18 257 ES, VdS approved
- Maximum resistance due to the layer construction: several bottom plates for maximum protection
- High impact resistance: extra long steel cams, complete with tempered special M6 screws
- An additional steel inset provides extra strong leverage/tear-off resistance
- Grip plate adjustable to DIN left and right doors
- Spacing: 92 mm, square bolt: 10 mm

Operation and use

- For main entrance doors
- Suitable for rebated and flush doors, left and right opening

HLT612 for front doors in F1: Aluminum (Handle plate/Door handle)

Seite 2 von 2

- Grip plate outside, handle inside
- Suitable for door thicknesses of 52 - 72 mm
- Mounting material for deviating door thicknesses can be supplied

Variants

- Finishes: F1 (alu anodized), F2 (silver anodized), F3 (anodized brass), F4 (anodized bronze)
- Alternatively available as a handle/handle set

Technical data - HLT612 for front doors in F1: Aluminum (Handle plate/Door handle)

| | |
|------------------------------|---------------------|
| Beidseitig Drücker | No |
| Cylinder protrusion | 12 mm |
| Door fitting for fire doors | No |
| Door type | Entry door |
| Interchangeable fitting | Yes |
| Security Level Home Security | 6 |
| Weight | 1421 g |
| colour | F1: Aluminum Nature |
| pulling protection | No |
| EAN | 4003318247910 |