

# Wall-mounted AEBasic evaluation unit

Art.-Nr. 501638

Seite 1 von 2



The AEB evaluation units from ABUS Security-Center are the intelligent intermediaries between the door and alarm system and thus signify an increase in security and comfort during operation.

## Technologies

- AEBasic evaluation unit for arming/disarming burglar alarm systems
- Blocking of locking systems (CLX-/ SLT-/ ZL- Alarm AEBasic) via 3 m wireless transmission
- Control of electrical switching functions: electrical door openers, motorized locks, lighting etc.
- Wall mounting

## Technical data - Wall-mounted AEBasic evaluation unit

Additional functions	Optional when arming/disarming: configuration with or without status notification from the burglar alarm system
Area of application	Control of electrical switching functions
Colour	White
Connections	Power supply, digital and analogue interface
Height	86 mm
Housing	Surface mounted
Housing material	Plastic
Language of instructions	EN
Language packing	EN
Length	30 mm
Material	Plastic casing
Max. humidity	80 %
Max. number of locking media	255

# Wall-mounted AEBasic evaluation unit

Art.-Nr. 501638

Seite 2 von 2

---

## Technical data - Wall-mounted AEBasic evaluation unit

Max. operating temperature indoors	60 °C
Max. operating temperature outdoors	60 °C
Min. operating temperature indoors	-10 °C
Min. operating temperature outdoors	-10 °C
Net weight	0,1563 kg
OSD language	English
Operating mode	Relay as normally closed or normally open contact
Power supply	Power supply via external power source (not included in scope of delivery): 9–24 V DC; Switching power of the changeover relay 24 V AC/DC, 0.3 A
Programming	Via Prog ACS or SKM
Width	86 mm