

Wall-mounted wireless receiver unit

Art.-Nr. 501640

Seite 1 von 2



This wireless receiver unit receives its commands directly from the CLX, SLT or ZL door systems wirelessly. It passes these commands on to the evaluation unit AE255F via a wire connection which is connected to the alarm system in turn. This makes wireless incorporation of the door systems possible without additional door wiring.

Technologies

- Wireless receiver unit for cable connection to evaluation unit AE255F
- For wireless connection to an electronic locking system (CLX-/ , SLT-/ , ZL- Alarm AE255F)
- Additional door wiring is not required.

Technical data - Wall-mounted wireless receiver unit

Area of application	For wireless connection to an electronic locking system
Colour	White
Connections	Power supply, digital interface
Height	86 mm
Housing	Surface mounted
Housing material	Plastic
Language of instructions	EN
Language packing	EN
Length	30 mm
Material	Plastic casing
Max. humidity	80 %
Max. operating temperature indoors	60 °C
Max. operating temperature outdoors	60 °C

Wall-mounted wireless receiver unit

Art.-Nr. 501640

Seite 2 von 2

Technical data - Wall-mounted wireless receiver unit

Min. operating temperature indoors	-10 °C
Min. operating temperature outdoors	-10 °C
Net weight	0,1481 kg
OSD language	English
Power supply	Power supply via AE255F evaluation unit
Width	86 mm