

# Flush-mounted wireless receiver unit

Art.-Nr. 501641

Seite 1 von 2



This wireless receiver unit receives its commands directly from the CLX, SLT or ZL door systems wirelessly. It passes these commands on to the evaluation unit AE255F via a wire connection which is connected to the alarm system in turn. This makes wireless incorporation of the door systems possible without additional door wiring.

## Technologies

- Wireless receiver unit for cable connection to evaluation unit AE255F
- For wireless connection to an electronic locking system (CLX-/ , SLT-/ , ZL- Alarm AE255F)
- Additional door wiring is not required.

## Technical data - Flush-mounted wireless receiver unit

Area of application	For wireless connection to an electronic locking system
Colour	White
Connections	Power supply, digital interface
Diameter	84,5 mm
Height	7 mm
Housing	Flush socket
Housing material	Plastic
Language of instructions	EN
Language packing	EN
Material	Plastic cover
Max. humidity	80 %
Max. operating temperature indoors	60 °C
Max. operating temperature outdoors	60 °C

# Flush-mounted wireless receiver unit

Art.-Nr. 501641

Seite 2 von 2

---

## Technical data - Flush-mounted wireless receiver unit

Min. operating temperature indoors	-10 °C
Min. operating temperature outdoors	-10 °C
Net weight	0,1417 kg
OSD language	English
Other dimensions	Plastic cover $\varnothing$ 84.5 mm, height 7 mm (for flush sockets $\varnothing$ 55 mm)
Power supply	Power supply via AE255F evaluation unit