

CodeLoxx Standard Security

Art.-Nr. CLX-LA-S-10

Seite 1 von 2



This premium electronic CodeLoxx cylinder provides more security, control and convenience at your door. It is operated using the read-protected ABUS Seccor chip key. The cylinder has additional plating for even more protection against break-ins. The unique modular extension system guarantees maximum flexibility during installation, use or structural changes.

Technologies

- Electronic double knob cylinder with chip key reader
- Premium stainless steel knobs
- Operation using ABUS Seccor chip key
- Reliable power supply
- Optical signalling
- Extremely tamper-proof cylinder thanks to ABUS Security drill protection
- Permanent access; opening time can be set between 6 and 12 sec.

Technical data - CodeLoxx Standard Security

Annual profiles	No
Area of application	Doors with PZ mortise lock, multiple locking, panic lock (approved for locking nose with free-wheel function)
Colour	Stainless steel
Combination code	No
DC voltage supply	3 V
Drill protection	Security
Electronics	Default
Emergency power supply possible	Yes
Event memory	1000
Inner knob diameter	33 mm
Inner knob length	45 mm
Locking media	ABUS-Seccor key reader
Logging and time function	No
Material	Stainless steel knobs, plastic cap inside
Max. number of locking media	511

CodeLoxx Standard Security

Art.-Nr. CLX-LA-S-10

Seite 2 von 2

Technical data - CodeLoxx Standard Security

Max. operating temperature indoors	60 °C
Max. operating temperature outdoors	60 °C
Min. operating temperature indoors	-10 °C
Min. operating temperature outdoors	-20 °C
Modularly extendible	Yes
Opening time can be set	between 6 and 12 seconds
Outer knob diameter	30 mm
Outer knob length	39 mm
Permanent access	Yes
Programming	Via programming key and/or PELT or SKM with TG-SKM
Protection class IP Indoor	44
Protection class IP Outdoor	55
Reader type	Chip key reader
Signalling	optical
Special design axle	For doors with PZ perforation
Standard length	Length measurement when ordering
Weekly profiles	No
ZAAP	No