

# IP Dome 4 MPx (2.8–12 mm)

Art.-Nr. IPCB74521

Seite 1 von 4



## STRONG OUTSIDE: IN ANY LIGHT. AGAINST MANIPULATION.

With 4 MPx resolution, weatherproof IP67 housing, IK10 vandal protection and powerful IR LEDs, the IP dome is the surveillance camera for 24/7 outdoor surveillance day and night. WDR dynamics and Ultra Low-Light ensure clear images in any light.

## Best, flexible surveillance in 4 MPx

The motorised zoom lens with 2.8-12 mm focal length covers a range of 30-108° (4.2x optical). Focal length and focus are conveniently and precisely adjusted via the web interface.

## Autom. Object recognition

The security camera reliably distinguishes relevant movements (people, vehicles) from disturbances (branches, light, etc.) and thus minimises unnecessary motion alarms.

## Recording and compatibility

Recordings are made on an ABUS recorder, on video management software or local microSD card. The camera is compatible with ABUS Secvest, Secoris and WLX Pro Plus.

## Convenient start-up

Suitable for mounting on ceiling or wall, also with protected wiring and for discreet ceiling installation (with installation box/holder). The free ABUS IP Installer software makes setup easier.

## ABUS Link Station app: Live Image & Push

For mobile access for live viewing, playback and push notifications for events. IPv6 compatible.

Notes: No power supply unit is included, as power is supplied via PoE.

# IP Dome 4 MPx (2.8–12 mm)

Art.-Nr. IPCB74521

Seite 2 von 4

The effective IR range will vary depending on the installation location.

## Technologies

- 4 MPx resolution (2,688 x 1,520 @ 25 fps) for crisp surveillance images
- 2.8 - 12 mm motorised zoom lens (4x optical zoom, 30°-108° viewing angle) for high flexibility in surveillance and choice of installation location
- Ultra low-light performance for excellent image results in poorly lit environments
- 120 dB WDR function to compensate for image contrasts, strong backlighting etc.
- Object recognition (human & vehicle): Motion detection with fully automatic differentiation between people/vehicles and disturbances (branches, light, etc.)
- Very robust, vandalism- and weather-proof housing (IK10 & IP67), in a discreet look with black covered components in the dome
- IR LEDs for very clear images in the dark (up to 40 m range)
- Supports H.264, H.265, MJPEG (incl. Dynamic GOP)
- MicroSD card slot for internal data storage
- 12 V DC & PoE (802.3af)

## Technical data - IP Dome 4 MPx (2.8–12 mm)

Alarm input (NO/NC)	1
Alarm output	1
Alarming	E-Mail, NAS, FTP, Sound
Audio	Connectable: Microphone, Loudspeaker
Backlight compensation	WDR, BLC, HLC
Camera type	Dome
Compatible with	ABUS NVR/DVR, ABUS Link Station App, Synology Surveillance Station 6.0.1+
Compatible with ABUS Link Station	Yes
Compatible with Comfion	Yes
Compatible with Secoris	Yes
Compatible with Secvest	Yes
Compatible with wAppLoxx	Yes
Compatible with wAppLoxx Pro	Yes
Connections	1 x RJ45, 1 x DC, 1 x Alarm input, 1 x Alarm output, 1 x Audio input, 1 x Audio output
DC voltage supply	12 (+/-25 %) V
Day/night switching	ICR/Color/B/W
Design	Dome
Digital zoom	Yes
Dimensions	(LxWxH) 154x154x112 mm

# IP Dome 4 MPx (2.8–12 mm)

Art.-Nr. IPCB74521

Seite 3 von 4

## Technical data - IP Dome 4 MPx (2.8–12 mm)

Dynamic range (WDR)	120 dB
Electronic shutter	1/3 - 1/1000000 s
Encryption	HTTPS, TLS 1.1/1.2
Focal length	2,8 – 12,0 mm
Frame rate	1/16, 1/8, 1/4, 1/2, 1, 2, 4, 6, 8, 10, 12, 15, 16, 18, 20, 22, 25, 30 fps
Functions	Scene Change Detection, Region of Interest
Gross weight	1,5 kg
Height	112 mm
Horizontal viewing angle	30 – 108 °
Housing material	Metal
ICR day/night function	Yes
IP protection class	67
IR LEDs	Yes
IR range (up to)	40 m
Image enhancement	WDR, BLC, HLC, 3D DNR, Vertical Display (not in Smart-Event mode)
Image sensor	1/2.7" Progressive Scan CMOS
Installation type	Ceiling, Wall
LAN network access	RJ45 10M/100M self-adaptive
Language of instructions	DE, UK, FR, NL, DK
Length	154 mm
Lens	Motor-Zoom
Max. humidity	95 %
Max. operating temperature	60 °C
Max. resolution @ frame rate	2688 x 1520 @ 30 fps
Microphone	No
Min. operating temperature	-25 °C
Minimum illumination (IR)	0 lx
Minimum illumination (colour)	0,003 lx
Motion detection	8 zones
Net weight	0,9 kg
Network camera protocols	IPv4/v6, HTTP, HTTPS, FTP, SMTP, UPnP, DNS, DynDNS, NTP, RTSP, TCP, UDP, DHCP, ABUS Server, P2P, QoS, 802.1X, IGMP, Bonjour, PPPoE, SNMP
Noise reduction	3D DNR
Number of IR LEDs	2
Number of streams	3
Number of users	32
ONVIF	Profile G, S, T
OSD language	DE, UK, FR, NL, DK, IT

# IP Dome 4 MPx (2.8–12 mm)

Art.-Nr. IPCB74521

Seite 4 von 4

## Technical data - IP Dome 4 MPx (2.8–12 mm)

Optical zoom	4,2 x
Other functions	Object Classification Person/Vehicle
Pixels (effective)	2688(H) x 1520(V) pixel
PoE standard	IEEE 802.3af
Power consumption	1.100 mA
Private zones	4
Protection class IK	10
Resolution	4 MP
Resolution modes	Stream 1: 2688 x 1520 @ 25 fps, Stream 2: 640 x 480 @ 25 fps, Stream 3: 1920 x 1080 @ 10 fps
Storage medium	microSD card, 256 GB (opt.)
Supported browsers	IE11, Mozilla Firefox, Google Chrome, MS Edge
Technology	IP
Vertical viewing angle	17 – 56 °
Video Content Analysis (VCA)	Tripwire Detection, Intrusion Detection, Region Entrance, Region Exit
Video compression	Stream 1: H.264, H.265, Dynamic GOP (+), Stream 2: H.264, H.265, MJPEG, Stream 3: H.264, H.265
Video network bandwidth	32 kBit/s - 8 MBit/s
White balance	AWB, Manual
Width	154 mm