

SRG92N for tubular frame doors in F1: Aluminum (Handle plate/Door handle)

Seite 1 von 2



Technologies

- Distance of cams adjustable to most common drilling patterns
- Handle on inside automatically returns to initial position
- Fixing screws hidden by decorative aluminium plate
- For cylinder protrusions of 12 mm
- Spacing: 92 mm, square bolt: 8 mm
- Easy fitting

Operation and use

- For universal use on narrow frames
- Grip plate outside, handle inside
- Suitable for door thicknesses of 57 - 65 mm

Variants

- Finishes: F1 (alu anodized), F2 (silver anodized), stainless steel look, white
- Alternatively available as a handle/handle set

Technical data - SRG92N for tubular frame doors in F1: Aluminum (Handle plate/Door handle)

Beidseitig Drücker	No
Cylinder protrusion	12 mm
Door fitting for fire doors	No
Door type	Doors with tubular frames
Interchangeable fitting	Yes
Security Level Home Security	5
Weight	1074 g

SRG92N for tubular frame doors in F1: Aluminum (Handle plate/Door handle)

Seite 2 von 2

Technical data - SRG92N for tubular frame doors in F1: Aluminum (Handle plate/Door handle)

colour	F1: Aluminum Nature
pulling protection	No
EAN	4003318625541