

KLZS714 square for flat entrance doors in F1: Aluminum (Handle plate/Door handle)

Seite 1 von 2



FEEL SECURE AT HOME

House front doors and flat doors become more secure with this door fitting.

Inadequately secured doors make your home an easy target for burglars. Common security vulnerability: Door cylinders that stick out too far and can be easily unscrewed. Secure your doors with a reliable door fitting. Make your butt and rebated doors more secure with this door hardware. It consists of several layers of steel and can withstand a tensile load of 2.5 tonnes. It excels especially against pulling off the cylinder. Extra long steel cams with hardened and tempered special M6 screws also increase protection against impact. A steel insert in the outer handle reliably prevents tearing. A secure complete package with VdS and DIN certificate for house front doors (HLZS) with a thickness of 52 to 72 millimetres and flat front doors (KLZS) with a thickness of 37 to 47 millimetres.

Technologies

- Certified according to DIN EN 1906 SK 2 and DIN 18 257 ES 1 ZA, VdS approved
- High resistance due to the layer construction: several bottom plates, with a total of 13.5 mm thickness, for high protection
- High impact resistance: extra long steel cams, complete with tempered special screws (3 x M6)
- An additional steel inset provides extra strong leverage/tear-off resistance
- Integrated pulling protection with cylinder cover plus freely rotating special steel disc
- Grip plate adjustable to DIN left and right doors
- spacing: 72 mm, square bolt: 8 mm

Operation and use

KLZS714 square for flat entrance doors in F1: Aluminum (Handle plate/Door handle)

Seite 2 von 2

- For main entrance doors (HLZS) and apartment doors (KLZS)
- Suitable for rebated and flush doors, left and right opening
- Grip plate outside, handle inside
- Suitable for door thicknesses of 37 - 47 mm
- Mounting material for deviating door thicknesses can be supplied

Variants

- Finishes: F1 (alu anodized), F2 (silver anodized), F3 (anodized brass), F4 (anodized bronze)
- Alternatively available as a handle/handle set

Technical data - KLZS714 square for flat entrance doors in F1: Aluminum (Handle plate/Door handle)

Beidseitig Drücker	No
Cylinder protrusion	10-18 mm
Door fitting for fire doors	No
Door type	Apartment door
Interchangeable fitting	Yes
Security Level Home Security	8
Weight	1376 g
colour	F1: Aluminum Nature
pulling protection	Yes
EAN	4003318203541