



Help yourself! Controllable video surveillance for analogue cameras. This ergonomically designed and robustly made control panel enables simple control of up to 255 motor domes via RS-485. The integrated LCD display enables you to monitor each of your control steps. One special feature is the additional option to directly control several recorders. Direct access to the OSD of the connected dome is also possible. With the ABUS DVR control panel you can manage up to 31 recorders simultaneously.

## Technologies

- 3D joystick with zoom in/out function
- Direct control of a DVR possible
- Direct access to the OSD of the dome possible
- LCD display
- RS485 interface

## Technical data - DVR/PTZ Controller

|                            |                                |
|----------------------------|--------------------------------|
| Certifications             | CE                             |
| Connectible devices        | 255 PTZ / 31 DVR               |
| Connections                | RS-485                         |
| DC voltage supply          | 12 V                           |
| Dimensions                 | (W x H x D) 360 x 108 x 200 mm |
| Gross weight               | 3,45 kg                        |
| Height                     | 108 mm                         |
| LED display                | Yes                            |
| Length                     | 200 mm                         |
| Max. operating temperature | 55 °C                          |
| Min. operating temperature | -10 °C                         |
| Net weight                 | 3,3 kg                         |
| Transmission distance      | 1.200 m                        |
| Width                      | 360 mm                         |