

Day/Night Mini Outdoor Dome Camera

Art.-Nr. TVCC34010

Seite 1 von 2



Unobtrusive monitoring indoors or outdoors

The analogue day/night outdoor dome camera is the ideal supplement to the TWR30004 4-channel recorder and the TVVR30104 video surveillance kit. It stands out with its plain design and high protection class (IP66), which means it can be used both outdoors and indoors. The camera has integrated IR LEDs for 24/7 use both day and night. With a high, detailed resolution of 600 TVL, it delivers precise video images for accurate recognition of persons.

Flexible mounting options

Fast and easy installation is guaranteed with the 20 m combination cable and power supply unit provided.

The effective IR range will depend on the installation location. If there are surfaces that absorb light or no objects that reflect IR light in the field of view, the IR range will be reduced and/or the video image will be too dark. Reflective objects in the immediate vicinity of the camera (e.g. roof gutter or wall) may also result in the reflection of IR light, which can disturb the image.

Technologies

- Compact day/night vision mini outdoor dome camera
- Varied camera installation options - whether indoors or outdoors
- Simple design and high protection class (IP66)
- High detailed resolution, thanks to 600 TVL
- 1 x 20 metre coaxial cable included
- Ideal for extension of TVVR30004 or TVVR30104

Day/Night Mini Outdoor Dome Camera

Art.-Nr. TVCC34010

Seite 2 von 2

Technical data - Day/Night Mini Outdoor Dome Camera

| | |
|-------------------------------|---------------------------------|
| DC voltage supply | 12 V |
| Day/night switching | Electromechanical IR-cut filter |
| Dimensions | 59 x 83 x 90 mm |
| Focal length | 3.6 mm |
| Horizontal viewing angle | 68,4 ° |
| IP protection class | 66 |
| IR LEDs | Yes |
| IR range (up to) | 10 m |
| Image sensor | 1/3" DIS |
| Max. humidity | 90 % |
| Max. operating temperature | 50 °C |
| Min. operating temperature | -20 °C |
| Minimum illumination (IR) | 0 lx |
| Minimum illumination (colour) | 0,1 lx |
| Noise reduction | > 52 dB |