

Analogue HD Mini Dome 3 MPx (2.8 mm)

Art.-Nr. HDCC33500

Seite 1 von 2



ABUS Analogue HD: Analogue images have never been so clear

The Analogue HD Mini Dome 3 MPx has a high-quality image sensor for the surveillance of extensive indoor and outdoor areas. This ensures it provides a razor sharp and fluid image, for better detail recognition. The Analogue HD Mini Dome 3 MPx with True WDR A high-performance True WDR function ensures evenly lit foregrounds and backgrounds in high-contrast light situations.

24/7 indoor and outdoor surveillance

The automatic day/night switching offered by the improved IR LED technology provides for better image lighting under varying light conditions. The Analogue HD Mini Dome is robust in the face of wind and weather thanks to its IP67 protection class.

Analogue HD technology: Ideal for inexpensive retrofitting

Using the infrastructure already installed offers flexible retrofitting possibilities. Simply exchange the cameras and recorders and get better performance from your existing video surveillance systems. You can continue to use your existing coaxial or 2-wire cable.

The effective IR range will depend on the installation location. If there are surfaces that absorb light or no objects that reflect IR light in the field of view, the IR range will be reduced and/or the video image will be too dark. Reflective objects in the immediate vicinity of the camera (e.g. roof gutter or wall) may also result in the reflection of IR light, which can disturb the image.

Technologies

- 3 MPx Resolution: 1920 x 1536 @ 18 fps
- 42 % more image data compared to 2 MPx

Analogue HD Mini Dome 3 MPx (2.8 mm)



Art.-Nr. HDCC33500

Seite 2 von 2

-
- True WDR functionality effectively compensates for light/dark contrast
 - Fixed lens (2.8 mm)
 - Powerful IR LED technology for improved illumination of up to 20 m at night
 - Weatherproof (IP67) for outdoor use
 - Perfect for retrofitting: Transmission using conventional and existing CCTV infrastructure, such as coaxial or 2-wire cables
 - Cable length of up to 500 m possible without loss
 - Wide variety of holders for straightforward, cost-efficient installation
 - Only compatible with Analogue HD Video Recorder HDCC90001, HDCC90011 and HDCC90021
-