

# 4043158144000



Security Tech Germany

Art.-Nr. PPDF18000R

Seite 1 von 2

## Technical data - 4043158144000

Alarming	Push notification / Acoustic warning signal
Channel width	3 MHz
Colour	White
Compatible with Secvest	No
Compatible with Smartvest	No
Compatible with wAppLoxx	No
Connections	Power: DC plug / Network: RJ45 socket / 2x USB 2.0 / HDMI 1.2
DC voltage supply	12 V
Dimensions	(W x L x H) 200 x 200 x 50 mm
Encryption	FHSS Hardware-Encryption, AES256
Frequency range	2,403 - 2,478 GHz
Gross weight	2,086 kg
Housing material	Plastic
Loudspeaker	No (Audio via HDMI)
Max. operating temperature	40 °C
Microphone	No
Min. operating temperature	0 °C
Modulation	FHSS, GFSK
Monitor type	LCD Touchscreen
Net weight	0,5 kg
Network access	RJ45 10/100Mbps
Network protocols	TCP, UDP, UPNP
Number of channels	4
Number of simultaneous accesses	3
OSD language	DE, GB, FR, NL, DK, IT, PL
Plug type	DC-plug: 5,5 x 2,5mm
Power consumption	2 W
Recording modes	Manual, schedule, motion detection
Recording resolution @ frame rate per camera	1Ch: Full HD (1080p) @ 30fps / 2Ch: Full HD (1080p) @ 15fps / 3-4Ch: HD (720p) @ 30fps
Resolution HDMI output	Full HD (1080p)
Resolution modes	Full HD (1080p) / HD (720p)
Sensitivity	-80 dBm
Software	APP: ABUS OneLook (Android/iOS)
Storage medium	MicroSD (max. 128GB), external USB hard drive (max. 2TB)
Technology	Radio
Transmission channels	26

# 4043158144000



Art.-Nr. PPDF18000R

Seite 2 von 2

---

## Technical data - 4043158144000

Transmission power	20 dBm
Video compression	H.246
Views	1, 1+1, 1+3, 2+2
Wireless range	(Depending on installation) 20 - 50 m