ABUS Z-Wave Gateway



Art.-Nr. SHGW10000 Seite 1 von 2



The ABUS Z-Wave Gateway is versatile and grows in possibilities with your requirements. Start with ABUS sensors and actuators to protect yourself from hazards. You can also integrate third-party solutions to save energy or regulate heating, for example. In conjunction with the Smartvest wireless alarm system, you combine the convenience of the Connected Home with real security. The Smartvest wireless alarm system remains an absolutely self-sufficient security solution. Via the ABUS Z-Wave Gateway, it opens up to the entire Z-Wave world and the safety logic remains unaffected.

Technologies

- · Compact smart home control unit in Family Home Design with Z-Wave radio standard
- extendable to a maximum of 120 Z-Wave radio components
- compatible to the ABUS Smartvest Wireless Alarm System
- extensive configuration options for up to 60 Scenes (if then when)
- Mobile access from any location via the free app ABUS Z-Wave ONE (for iOS and Android)
- Instant alerting via push notification via app Up to 1,000 events can be stored
- Data protection: All personal data is stored locally in the gateway
- Control by voice command possible (via Google Home or Amazon Alexa)

Technical data - ABUS Z-Wave Gateway

| Alarming | Push notification / Acoustic warning signal |
|---------------------------|---------------------------------------------|
| Backup power supply | No |
| Colour | White |
| Compatible with | Z-Wave devices (EU frequency: 868.42MHz) |
| Compatible with Secvest | No |
| Compatible with Smartvest | Yes |
| DC voltage supply | 5 V |





Art.-Nr. SHGW10000 Seite 2 von 2

Technical data - ABUS Z-Wave Gateway

| Dimensions | (B x L x H) 96 x 21 x 96 mm |
|-----------------------------|----------------------------------------|
| Display | LED |
| Encryption | AES128, SFTP, HTTPS |
| Gross weight | 0,38 kg |
| Housing material | Plastic |
| Loudspeaker | Yes |
| Luminous colour | Blue / Yellow / Red |
| Max. humidity | 80 % |
| Max. operating temperature | 50 °C |
| Min. humidity | 20 |
| Min. operating temperature | 0 °C |
| Net weight | 0,233 kg |
| Network access | RJ-45 connector (10/100 Mbps) |
| Number of components | 120 |
| Number of events | 1.000 |
| Number of rooms / groups | 40 |
| Number of scenes | 60 |
| Number of users | 15 |
| Radio frequency | 868,42 MHz |
| Radio modulation | Z-Wave Plus (S2) / FSK (BFSK / GFSK) |
| Simultaneous network access | 10 |
| Software | App: ABUS Z-Wave One (Android / iOS) |
| Transmission power | 4,5 dBm |
| User levels | 3 |
| Wireless range | (Depending on installation) 20 - 100 m |