

21.5" LED Monitor with BNC Input

Art.-Nr. TVAC10014

Seite 1 von 2



21" LED MONITOR (1080p)

The high-resolution monitor for countless applications in video surveillance, offices and industry. Its high picture quality and versatile connection options make it the optimal monitor for surveillance recorders, PCs or directly connected analogue cameras.

With full HD resolution of 1,920 x 1,080 pixels in 16:9 format (1080p), the LED monitor delivers brilliant colour reproduction and high contrast for razor-sharp images in live view and playback. Thanks to LED backlighting, details and colours are displayed particularly precisely and true to life. At the same time, the power consumption is very low and the life of the screen is longer than with conventional monitors.

Easy to connect and flexible to use: the monitor is quickly and easily connected to a surveillance recorder or PC via an HDMI connection. Its 2 BNC inputs and outputs each are compatible with the common analogue video standards (HD-TVI, HD-CVI, AHD and CVBS). In this way, corresponding security cameras can also be connected directly via Plug & Play, e.g. for live surveillance. The monitor is also compatible with commercially available VESA brackets for easy wall mounting. This saves space at the workplace (desk, counter, gate) and allows easy installation of the unit as a spot or confrontation monitor, e.g. in retail, logistics or service.

Technologies

- High-contrast 21" LED monitor with bright colour display (16:9 format)
- Full HD resolution: 1.920 x 1.080 pixels
- Connections: 1 x HDMI, 2x BNC input and output for HD-TVI, HD-CVI, AHD and CVBS
- Plug & Play with all conventional analogue technologies
- LED backlighting: Brilliant colour display and high contrast
- Compatible with VESA brackets

21.5" LED Monitor with BNC Input

Art.-Nr. TVAC10014

Seite 2 von 2

Technical data - 21.5" LED Monitor with BNC Input

Brightness	250 cd/m ²
Colour levels	16,7
Comb filter	3D
Connections	1 x HDMI, 2x BNC in/out (TVI, CVI, AHD, CVBS)
Contrast ratio	1000:1
DC voltage supply	12 V
Dimensions	490 x 359 x 147 mm
Display surface	matte
Gross weight	4,1 kg
Height	359 mm
Housing material	Plastic
Image format	16:9
Input	1 x HDMI, 2x BNC (TVI, CVI, AHD, CVBS)
Length	147 mm
Max. humidity	90 %
Max. operating temperature	40 °C
Min. operating temperature	0 °C
Monitor type	LED
Net weight	3,7 kg
Power consumption	25 W
Reaction time	5 ms
Screen diagonal	21,5 in
Signal detection	Automatic
Viewing angle horizontal/vertical	178° x 178°
Width	490 mm