

Additional camera for ABUS EasyLook BasicSet

Art.-Nr. PPDF17520 Seite 1 von 3



Up to 4 cameras per monitor

Add up to 4 cameras to your ABUS EasyLook BasicSet. Commissioning an additional camera is just as easy as with the basic set and done in just a few steps.

Just like the camera in the basic set, an additional camera reliably delivers video images day & night. The camera performs its job without internet/Wi-Fi, without an app and without a smartphone - all it needs is power. The video data and settings are securely encrypted and quickly transmitted wirelessly between the camera and the monitor of the basic set.

Commissioning the additional camera is just as easy as with the basic set. A total of up to 4 cameras can be easily operated with one monitor; if needed, the screen displays all live images from the cameras simultaneously - with a simple finger gesture, it is possible to quickly switch between the "quad view" and individual camera images.

So you always have a view of what is happening in your shop or around your home, whether at the entrance, in front of the garage, on the terrace or in the garden.

Technologies

- Extension for the ABUS EasyLook BasicSet; additional camera with high wireless range, reliable motion detection, intercom function, night vision, privacy zone masking and much more
- A total of 4 security cameras can be wirelessly connected to the monitor of the ABUS EasyLook BasicSet
- Very easy to use, even for subsequent commissioning; supply power to the additional camera, add it to the set monitor and the first live image will appear
- Inside and outside, the surveillance camera reliably detects people/animals thanks to its clever motion detection (integrated motion detector/passive infrared sensor, PIR for short, detects heat; camera software analyses for motion in parallel)
- Monitor immediately and automatically switches to alarm and recording mode (siren sound on the monitor can be



Additional camera for ABUS EasyLook BasicSet

Art.-Nr. PPDF17520 Seite 2 von 3

switched on/off as required; insert standard microSD card with up to 128 GB for storage)

- Personal settings via monitor; deactivate audio/sound for recordings (GDPR/data protection compliant), image areas with/without recognition, schedules, privacy zones
- Clear night vision in black and white (via infrared LED) up to 15 metres, 3-megapixel camera resolution, zoom function, 82-degree viewing angle, camera protection class IP66 (weatherproof; protection against strong jets of water, dustproof)
- No further costs (no subscription, no cloud)

Technical data - Additional camera for ABUS EasyLook BasicSet

| Base event | PIR & Software + Motion Mask |
|------------------------------|--|
| Channel width | 20 MHz |
| Colour | Black |
| Compatible with | PPDF17000 |
| Compatible with Secvest | No |
| Compatible with Smartvest | No |
| Compatible with wAppLoxx | No |
| DC voltage supply | 12 V |
| Day/night switching | Auto |
| Dimensions | (W x L x H) 61 x 161 x 77 mm |
| Encryption | WPA2 |
| Focal length | 4 mm |
| Frequency range | 2,403 - 2,478 GHz |
| Functions | Intercom (2-way audio), Night vision, People recognition, Zoom |
| Horizontal viewing angle | 82 ° |
| Housing material | Plastic |
| IP protection class | 66 |
| IR LEDs | Yes |
| IR range (up to) | 15 m |
| IR swivel filter | Yes |
| Image sensor | 1/3" CMOS |
| Loudspeaker | Yes |
| Max. humidity | 90 % |
| Max. operating temperature | 50 °C |
| Max. resolution @ frame rate | 2305 x 1296 @15fps |
| Microphone | Yes |
| Min. humidity | 30 |
| Min. operating temperature | -10 °C |
| Minimum illumination (IR) | 0,1 lx |
| Minimum illumination | 1 lx |
| (colour) | |



Additional camera for ABUS EasyLook BasicSet

Art.-Nr. PPDF17520 Seite 3 von 3

Technical data - Additional camera for ABUS EasyLook BasicSet

| Net weight | 0,3 kg |
|------------------------|---------------------------------------|
| Optical Wave Length | 940 nm |
| PIR range | 8 m |
| PIR viewing angle | 85 ° |
| Plug type | DC-plug: 5,5 x 2,1 mm |
| Power consumption | 3,6 W |
| Power supply | Power adapter |
| Private zones | 4 |
| Resolution modes | 2305 x 1296 (3MP) |
| Sensitivity | -88 dBm |
| System | Stand-alone Stand-alone |
| Technology | Wireless |
| Transmission power | 20 dBm |
| Vertical viewing angle | 42 ° |
| Video bit rate | 2Mbps |
| Video compression | H.264+ |
| White balance | Auto |
| Wireless range | (Depending on installation) 20 - 50 m |