

# ABUS 4MPx IP PoE Mini Tube Camera

Art.-Nr. TVIP64511

Seite 1 von 3



## Mini tube camera with powerful functions

Save time connecting. Discreet, reliable and clever monitoring. Save data.

## Cost-saving PoE technology

For company premises, business, office or home: The 4MPx IP PoE Mini Tube camera is ideal for indoor/outdoor use and discreet monitoring from the wall. Power can be supplied via network cable, e.g. router or recorder (Power over Ethernet, PoE) - esp. useful in hard-to-reach spots, saving installation costs.

## Efficient start-up & clever video surveillance

The surveillance camera differentiates fully automatically between person and vehicle - it only stores and reports what interests users. This and the strong data compression ensure highly efficient storage (recorder, NAS or microSD card). Even start-up is brief: Camera's user interface is quickly accessed from a PC/browser or recorder/monitor and ABUS IP Installer and displays the first live image within minutes. Settings can also be customised quickly (e.g. schedules, privacy zones, etc.).

## Powerful WDR function & IR LEDs for consistently sharp images

The IP camera also manages heavily fluctuating light conditions, e.g. strong backlight in entries or outdoors in general (WDR 120 dB). It also has infrared LEDs for good visibility in the dark/at night.

## Mobile app access

Users receive a push notification from the ABUS Link Station app in the event of a motion alarm. App's Pro version offers unlimited mobile access. Free with Lite version: up to 60 mins/month data stream (live view/playback).

## Technologies

- PoE surveillance camera for indoor and outdoor use, ideally placed on the wall; small, powerful and versatile security camera with professional features; stores on microSD, recorder/NVR or NAS
- Transfer video data to the router/switch/recorder extremely reliably via Power over Ethernet (PoE) with just one cable and keep the camera connected to power at the same time; optional power supply via 12 V DC plug-in power supply unit
- Lean start-up in just a few minutes using a PC/browser or recorder/monitor and free ABUS IP Installer (searches for

# ABUS 4MPx IP PoE Mini Tube Camera

Art.-Nr. TVIP64511

Seite 2 von 3

IP address of camera in home or company network)

- Fully automatic object recognition of person and vehicle, ignores interfering influences such as branches or light, in vid. Configuration via established user interface with schedules, privacy zones, etc.
- True WDR function (120 dB) for backlit situations, IR LEDs for night vision up to 30 metres (depending on location), wind & weatherproof (protection class IP67), QHD resolution (4 megapixels) and 103° viewing angle
- Compact dimensions/size (mini tube design, length 17 cm) ideal for discreet 24/7 video surveillance in the company or at home; motion detection means less storage space is required and users can quickly find the scenes they are looking for
- Records via microSD memory card (accessory), network video recorder (NVR) or NAS (Network Attached Storage); H.265 Plus video compression for longer recording with ultra-efficient storage space utilisation
- Easy mobile access to live stream and memory with smartphone/tablet via the ABUS Link Station app, incl. push notification when motion alarm is triggered (with no additional settings required on the router); option to get info/images via e-mail/FTP

## Technical data - ABUS 4MPx IP PoE Mini Tube Camera

Alarming	Push-To-App, E-Mail, FTP, microSD
Compatible with Secvest	Yes
Compatible with wAppLoxx	Yes
DC voltage supply	12 (+/-25 %) V
Day/night switching	ICR/Color/B/W
Design	Tube
Dimensions	(LxWxH) 170x70x69 mm
Dynamic range (WDR)	120 dB
Encryption	HTTPS, TLS 1.1/1.2
Focal length	2,8 mm
Gross weight	0,64 kg
Horizontal viewing angle	103 °
Housing material	Metal
IP protection class	67
IR LEDs	Yes
IR range (up to)	40 m
Image enhancement	WDR, BLC, HLC, 3D DNR, Vertical Display (only in surv. mode - no VCA)
Image sensor	1/3" Progressive Scan CMOS
Lens mount	M12
Max. humidity	95 %
Max. operating temperature	60 °C
Max. resolution @ frame rate	2688 x 1520 @ 30 fps
Microphone	No
Min. operating temperature	-25 °C

# ABUS 4MPx IP PoE Mini Tube Camera

Art.-Nr. TVIP64511

Seite 3 von 3

## Technical data - ABUS 4MPx IP PoE Mini Tube Camera

Minimum illumination (IR)	0 lx
Minimum illumination (colour)	0,005 lx
Net weight	0,5 kg
Noise reduction	3D DNR
Number of users	32
OSD language	DE, UK, FR, NL, DK, IT
PoE standard	IEEE 802.3af
Power consumption	6 W
Private zones	4
Resolution	4 MP
Resolution modes	Stream 1: 2688 x 1520 @ 25 fps, Stream 2: 640 x 480 @ 25 fps, Stream 3: 1920 x 1080 @ 10 fps
Storage medium	microSD card, 256 GB (opt.)
Supported browsers	Edge, Mozilla Firefox, Google Chrome
Technology	Network
Vertical viewing angle	55 °
Video Content Analysis (VCA)	Tripwire Detection, Intrusion Detection
Video compression	Stream 1: H.264, H.265, Dynamic GOP (+), Stream 2: H.264, H.265, MJPEG, Stream 3: H.264, H.265
White balance	AWB, Manual